



Measuring Instruments For Wireless Communications

Inspected by	Approval by
서용운	김광주

Inspection Record

Product		Inspection	
Description	Shield Box	Date of Test	2022-05-26
Model No.	TC-5510A	Temperature	25 ±2 °C
Serial No.	5510A010101	Humidity	< 55%

1. Shield Effect

Equipment Used:

Model Number	Model Description	Serial No.
MS2663C	Spectrum Analyzer	6200050489
TC-92020A	Dipole Antenna(900MHz~1.8GHz)	-
TC-92040A	Dipole Antenna(2.4GHz)	-
TC-92030A	Sleeve Antenna(5.8GHz)	-
TC-94017A	Mini SG KIT	-
N5227A	Network Analyzer (Max. 67GHz)	-
-	Double Rigid Horn Antenna (6GHz ~ 67GHz)	-
Power AMP.	Benchtop RF System AMP.	RAMP00M65GA

Measurement Report

S/N	Frequency	Results			Remarks
		Min	Actual		
5510A010101	900MHz	-60dB	-88dB	Pass	PASS
	1800MHz	-60dB	-87dB	Pass	
	2400MHz	-70dB	-84dB	Pass	
	5800MHz	-70dB	-79dB	Pass	
	6GHz~18GHz	-55dB	-105dB	Pass	
	18GHz~32GHz	-55dB	-99dB	Pass	
	32GHz~40GHz	-55dB	-90dB	Pass	
	40GHz~50GHz	-55dB	-75dB	Pass	

* The shield effectiveness above is measured using TESCOM test module